

# » KISS 4U Short KTQ67/Flex «



## 4U Open Solution

- » Second Gen Sandybridge CPUs
- » Embedded Flex ATX Mainboard supporting AMT
- » Up to 16 GB DDR3
- » Supporting KISS Stor and KISS DAxx

## KISS 4U Short KTQ67/Flex

### Kontron Industrial Silent Server

The KISS 4U Short has been designed with flexibility in mind and can accommodate Flex ATX motherboards, all in a case that can be used as a tower, desktop or 19" rack mounted chassis. The main attraction of KISS servers is their extremely low noise level: they are inaudible against normal conversation. KISS IPC servers are therefore ideal for most noise-sensitive environments, such as hospital operating theaters and computer server rooms. The performance and configuration of

KISS servers are based on Kontron's extensive range of CPU boards and backplanes, which allows them to be adapted to meet a very wide range of requirements. Redundant PSUs, RAID Subsystem KISS Stor and Remote Diagnostic Software make KISS family a high reliable and contiguous operating industrial Server. Extra accessories adapt KISS to precisely meet your specific requirements.

Technical Information	
<b>System</b>	KISS 4U Short KTQ67/Flex
<b>Product Line</b>	KISS 4U Short V2
<b>Dimension (H x W x D)</b>	177 x 482 x 300 mm (4U x 19" x 11,81")
<b>Weight</b>	Approx. 12 kg
<b>Interfaces Front</b>	2x USB 2.0
<b>Interfaces of the installed board (rear)</b>	6x USB, 3x GB LAN, 2x RS232, 1x VGA, 2x Display Port, HD Audio
<b>Controls on the frontside</b>	Power button
<b>External accessible drive bays</b>	2x 5.25" 1x 3.5" 1x Slim Line
<b>Internal drive bays</b>	1x 3.5" (no SLIM Line)
<b>Power supply</b>	AC 400 W (80+) optional DC 24V or DC 48V
<b>Expansion slots</b>	1X PCI_e x16, 1X PCI_e x4, 2x PCI 32 Bit
<b>Memory</b>	Up to 32 GB DDR3
<b>Processor</b>	2nd Generation Intel® i7-, i5, -i3
<b>Temperature</b>	
Non-operating	-20°C to 70°C (-4°F to 158°F)
Operating	0°C to 55°C (60 °C at 10% POH per month)
<b>Humidity</b>	
Non-operating	10-90 %
Operating	10-95 % rel humidity non condensing
<b>Shock</b>	
Non-operating	30g, 11ms
Operating	15g, 11ms
<b>Vibration</b>	
Operating	10-500 Hz, 1g
Storage	10-500 Hz, 2g
<b>Noise</b>	< 35 dBA
<b>Approvals</b>	CE, designed to meets UL
<b>MTBF</b>	50,000 h
<b>Protection Class</b>	IP 20 front , optional IP 52
<b>Options</b>	DVD ROM, DVD RW KISS Stor1, KISS Stor 0/5

### CORPORATE OFFICES

#### Europe, Middle East & Africa

Lise-Meitner-Str. 3-5  
86156 Augsburg  
Germany

Tel.: +49 (0) 821 4086-0  
Fax: +49 (0) 821 4086 111  
sales@kontron.com

#### North America

14118 Stowe Drive  
Poway, CA 92064-7147  
USA

Tel.: +1 888 294 4558  
Fax: +1 858 677 0898  
info@us.kontron.com

#### Asia Pacific

17 Building,Block #1, ABP.  
188 Southern West 4th Ring Road  
Beijing 100070, P.R.China

Tel.: +86 10 63751188  
Fax: +86 10 83682438  
info@kontron.cn