

# ► Inline-P3\_e



DIN Rail

Fieldbus

Embedded OS



- **Fan Less**  
without fan up to PIII 933 MHz
- **Fieldbus on board**  
Can open, Device Net or Profibus
- **High Scalable**  
3x PC/104 extension

## ➤ Product Overview

Fanless DIN Rail mount PC, Fieldbus inclusive with Processors up to PIII 933 MHz, high shock and vibration as well Temperature Specification. Inline-P3 is the first choice as peripheral IPC in rough Industrial environment. If it is fanless it is Inline.

## ➤ Technical Information

Expansion Slots	3x PC/104
Drivers	HDD optional
OS	Windows XP Embedded Win XP
Power Supply	24 VDC +/-20%
Mounting	DIN Rail, optional Wall Mount
Temperature operating	0° to +50°C
Non operating	-25° to +70°C
Humidity	5-95% (non condensing)
Dimensions (W x H x D)	270mm x 196mm x 87,4mm
Cooling	Fanless

Processor	Pentium III 933 MHz
Memory	up to 512 MB mit Pentium III
Compact Flash	up to 4 GB
I/Os	2x USB PS/2 Mouse and Keyboard 1x LPT 2x LAN 10/100 Base-TX 4x RS 232 1x CRT DVI-D optional
Fieldbus	CanOpen, DeviceNet, Profibus oder MDI optional CAN (SIA1000)



## ➤ Corporate Offices

EMEA  
Kontron AG  
Oskar-von-Miller-Straße 1  
85386 Eching

Tel: +49 (0)8165/77 0  
Fax: +49 (0)8165/77 279  
sales@kontron.com

NORTH AMERICA  
Kontron America Corporate Office  
14118 Stowe Drive  
Poway CA, 92064-7147

Tel: (858) 677-0877  
Fax: (858) 677-0898  
sales@kontron.com

Asia Pacific  
4F, No. 415, Ti-Ding Blvd.  
Sec. 2, NeiHu District  
Taipei, Taiwan 114

Tel: +886 2 2799 2789  
Fax: +886 2 2799 7399  
sales@kontron.com.tw