

» KISS 1U PCI-960 «









1U Open Solution

- » Core™ Solo, Core™2 Duo
- » Shock protected Drive bays
- » 2 x PCI 32 bit full size
- » 1 x PCI_e x 16, 1 x PCI_e x 4 fullsize

#KDS 1U PCI 960# 05132011PDI All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is All data is for information purposes only and not guaranteed for legal purposes. Subject to change without in this datasheet trademarks of their respective owners.

KISS 1U PCI-960

1U Kontron Industrial Silent Server

The KISS 1U system has been designed with flexibility in mind and can accomodate PICMG 1.3, all in a chassis that can be used as desktop or 19" rack mounted cabinet. The main attraction of KISS 1U servers is their extremely low noise level, which is inaudible against normal conversation.

KISS IPC servers are thus ideal for most noise-sensitive environments such as hospital operating theaters and computer server rooms. The performance and maximum of configuration of KISS servers are based on Kontron's extensive range of CPU boards and backplanes, which allows them to be adapted to meet a very wide range of requirements.

System	KISS 1U PCI-960	
Product Line	KISS 1U	
Dimension (H x W x D)	44 mm x 482 mm x 457.2 mm (1U x 19" x 18")	
Weight	Approx. 10 kg	
Interfaces Front	4 x USB, 1 x LAN 10/100/1000	
Interfaces of the installed board (rear)	2 x USB	
- The state of the state (cas)	2 x LAN 10/100/1000	
	1 x VGA	
	2 x RS232	
Controls on the frontside	ATX Switch	
External accessible drive bays	1 x 3.5", 1 SLIM Bay	
Internal drive bays	1 x 3.5"	
Power supply	100-240 V AC, 300 W wide Range, 24 VDC, 48 VDC	
Expansion slots	2 x PCI 32 Bit 33 MHz fullsize	
	optional 1 x PCI_e x 16, 1 x PCI_e x 4	
Memory	up to 4 GB DDR2 (3GB usable)	
Processor	Celeron 440 (1,86 GHz)	
	T2500 (2 x 2,0 GHz)	
	T7400 (2 x 2,16 GHz)	
Temperature		
non-operating	-20°C - +70°C	
operating	0°C - +50°C	
Humidity		
non-operating	10-90 %	
operating	20-90 %	
Shock		
non-operating	30g, 11ms	
operating	20g, 11ms	
Vibration		
operating	1g 10-500 Hz	
storage	2g 10-500 Hz	
Noise	< 35dBA	
Approvals	CE, designed to meet UL	
MTBF	50.000 h	
Protection Class	IP 20 optional IP 52	
Options	FDD 3,5", Slide Rails, DVD ROM SLIM, KISS Stor Slim, Two additional SATA II HDDS (blocks full length espansion Slots,2 half size cards still possible)	

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1 85386 Eching/Munich Germany

Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive Poway, CA 92064-7147 USA

Tel.: +1 888 294 4558 Fax: +1 858 677 0898 info@us.kontron.com

Asia Pacific

17 Building,Block #1,ABP. 188 Southern West 4th Ring Road Beijing 100070, P.R.China

Tel.: + 86 10 63751188 Fax: + 86 10 83682438 info@kontron.cn

