

» KISS 2U PCI-759 «









2U Open Solution

- » Core™ Duo, Core™2 Duo
- » Shock protected Drive bays
- » PCI / ISA support
- » RAID1 Subsystem KISS Stor Slim

#KDS 2U - PGT 759# 05282009BC All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is All data is for information purposes only and not guaranteed for legal purposes. All band or product names are trademarks or registered trademarks of their respective owners.

KISS 2U PCI-759

2U Kontron Industrial Silent Server

The KISS 2U system has been designed with flexibility in mind and can accomodate PICMG 1.0, PICMG 1.3, FlexATX motherboards, all in a chassis that can be used as desktop or 19" rack mounted cabinet. The main attraction of KISS 2U servers is their extremely low noise level, which is inaudible against normal conversation.

KISS IPC servers are thus ideal for most noisesensitive environments such as hospital operating theaters and computer server rooms. The performance and maximum of configuration of KISS servers are based on Kontron's extensive range of CPU boards and backplanes, which allows them to be adapted to meet a very wide range of requirements.

Technical Information	
System	KISS 2U PCI-759
Product Line	KISS 2U
Dimension (H x W x D)	88 mm x 482 mm x 472 mm (2U x 19" x 18.58")
Weight	Approx. 10 kg
Interfaces Front	2 x USB 2.0
Interfaces of the installed board (rear)	1 x VGA, 2 x USB 2.0, 2 x LAN 10/100/1000
Controls on the frontside	ATX Switch, Reset
External accessible drive bays	1 x 5.25", 1 x 3.5"
Internal drive bays	1 x 3.5"
Power supply	100-240 V AC, 300 W wide Range
	100-240 AC 250 W redundant PSU
Expansion slots	3 x PCI 32 Bit fullsize, 1x PCI_e x16, 1x PCI_e x4
Memory	Up to 4 GB DDR 2
Processor	Core 2 Duo E4300
	Core 2 Duo E6400
Temperature	
non-operating	-20°C - +70°C
operating	0°C - +50°C
Humidity	
non-operating	10-90 %
operating	20-90 %
Shock	
non-operating	30g, 11ms
operating	15g, 11ms
Vibration	
operating	1g 10-500 Hz
storage	2g 10-500 Hz
Noise	~40db
Approvals	CE, desigend to meet UL
MTBF	50.000 h
Protection Class	Front IP20
Options	DVD ROM, DVD R/W
	Slide Rails, KISS Stor Slim

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1 85386 Eching/Munich Germany

Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive Poway, CA 92064-7147 USA

Tel.: +1 888 294 4558 Fax: +1 858 677 0898 info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP. 188 Southern West 4th Ring Road Beijing 100070, P.R.China

Tel.: + 86 10 63751188 Fax: + 86 10 83682438 info@kontron.cn

