

## Configuration Guide KISS 2U Short 986LCD-M/mITX



Categories	Select one each category	
<b>Mainboard</b>	986LCD-M/mITX	
<b>Processors Core Duo</b>	T7400 Core 2 Duo ( 2* 2,16GHz)	
	T2500 Core Duo(2* 2,0 GHz)	
	Celeron 440(1 * 1,86GHz)	
<b>Memory</b>	1 GB DDR II	
	2 GB DDR II	
<b>Drivebay 1</b>	No	
<b>Frontaccessible 5,25"</b>	DVD ROM SATA	
	DVD -R/RW SATA	
	RAID 1 subsystem KISS Stor Slim	
<b>Drivebay 2</b>	No	
<b>3,5" internal</b>	HDD SATA 160GB	
	HDD SATA 250GB	
	HDD SATA 500GB	
<b>accessible</b>	Dual CF Adapter 1* 1 GB CF	
	Dual CF Adapter 1* 2 GB CF	
	Dual CF Adapter 1* 4 GB CF	
<b>Second CF</b>	No	
	1 GB	
	2 GB	
	4 GB	
<b>Powersupplies</b>	AC 300W	
<b>Networkadapter</b>	NO	
	PCI card 1 x RJ45 10/100 base T	
<b>Graphic Adapter</b>	NO	
	PCI 32 MB(Dual DVI)	
<b>Options</b>	No	
	Custom Color	
	Slide Rails	
	others on request	
<b>Preinstalled OS</b>	No	
	Windows XP Multilingual	
	Linux Suse	
	WIN 2003 Server	
	Others on request	
<b>Variant</b>	Desktop	
	19" Rack Mount	